

**TPS 5.08/02/90 5.0SN GN BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**General ordering data**

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| Order No.    | <a href="#">2651900000</a>                                                         |
| Type         | TPS 5.08/02/90 5.0SN GN BX                                                         |
| GTIN (EAN)   | 4050118635072                                                                      |
| Qty.         | 200 pc(s).                                                                         |
| Product data | IEC: 630 V / 20 A / 0.05 - 4 mm <sup>2</sup><br>UL: 300 V / 15 A / AWG 30 - AWG 12 |
| Packaging    | Box                                                                                |

## TPS 5.08/02/90 5.0SN GN BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |
|------------|-------|
| Net weight | 3.9 g |
|------------|-------|

## System parameters

|                                 |                             |                                |                          |
|---------------------------------|-----------------------------|--------------------------------|--------------------------|
| Product family                  | OMNIMATE basic – Series TPS | Wire connection method         | Clamping yoke connection |
| Mounting onto the PCB           | THT solder connection       | Conductor outlet direction     | 90°                      |
| Pitch in mm (P)                 | 5.08 mm                     | Pitch in inches (P)            | 0.2 inch                 |
| Number of poles                 | 2                           | Pin series quantity            | 1                        |
| Solder pin length (l)           | 5 mm                        | Solder pin dimensions          | 0.8 x 1.0 mm             |
| Solder eyelet hole diameter (D) | 1.5 mm                      | Number of solder pins per pole | 1                        |
| Screwdriver blade               | 0.6 x 3.5                   | Tightening torque, min.        | 0.5 Nm                   |
| Tightening torque, max.         | 0.55 Nm                     | Clamping screw                 | M 3                      |
| Stripping length                | 8.5 mm                      | L1 in mm                       | 5.08 mm                  |
| L1 in inches                    | 0.2 inch                    |                                |                          |

## Material data

|                             |          |                             |              |
|-----------------------------|----------|-----------------------------|--------------|
| Insulating material         | PA       | Colour                      | Pale green   |
| Colour chart (similar)      | RAL 6021 | Insulating material group   | I            |
| UL 94 flammability rating   | V-0      | Contact material            | Copper alloy |
| Contact surface             | tinned   | Tinning type                | matt         |
| Storage temperature, min.   | -40 °C   | Storage temperature, max.   | 70 °C        |
| Operating temperature, min. | -40 °C   | Operating temperature, max. | 105 °C       |

## Conductors suitable for connection

|                                                 |                      |                                                 |                     |
|-------------------------------------------------|----------------------|-------------------------------------------------|---------------------|
| Clamping range, min.                            | 0.2 mm <sup>2</sup>  | Clamping range, max.                            | 4 mm <sup>2</sup>   |
| Wire connection cross section AWG, min.         | AWG 30               | Wire connection cross section AWG, max.         | AWG 12              |
| Solid, min. H05(07) V-U                         | 0.05 mm <sup>2</sup> | Solid, max. H05(07) V-U                         | 2.5 mm <sup>2</sup> |
| Flexible, min. H05(07) V-K                      | 0.2 mm <sup>2</sup>  | Flexible, max. H05(07) V-K                      | 4 mm <sup>2</sup>   |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.2 mm <sup>2</sup>  | w. plastic collar ferrule, DIN 46228 pt 4, max. | 2.5 mm <sup>2</sup> |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.2 mm <sup>2</sup>  | w. wire end ferrule, DIN 46228 pt 1, max.       | 2.5 mm <sup>2</sup> |

## Rated data acc. to IEC

|                                                                           |       |                                                                       |       |
|---------------------------------------------------------------------------|-------|-----------------------------------------------------------------------|-------|
| Rated current, min. number of poles (Tu=20°C)                             | 20 A  | Rated voltage for surge voltage class / pollution degree II/2         | 630 V |
| Rated voltage for surge voltage class / pollution degree III/2            | 400 V | Rated voltage for surge voltage class / pollution degree III/3        | 250 V |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 4 kV  | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 4 kV  |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 4 kV  |                                                                       |       |

## TPS 5.08/02/90 5.0SN GN BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Rated data acc. to UL 1059

Institute (UR)



Certificate No. (UR)

E60693

Institute (cURus)



Certificate No. (cURus)

E60693

Rated voltage (Use group B / UL 1059) 300 V

Rated voltage (Use group D / UL 1059) 300 V

Rated current (Use group B / UL 1059) 15 A

Rated current (Use group D / UL 1059) 10 A

Wire cross-section, AWG, min. AWG 30

Wire cross-section, AWG, max. AWG 12

Reference to approval values  
Specifications are maximum values, details - see approval certificate.

## Packing

Packaging

Box

VPE length

170 mm

VPE width

135 mm

VPE height

50 mm

## Classifications

ETIM 6.0

EC002643

ETIM 7.0

EC002643

ECLASS 9.0

27-44-04-01

ECLASS 9.1

27-44-04-01

ECLASS 10.0

27-44-04-01

ECLASS 11.0

27-46-01-01

## Important note

Notes

- Only compatible with OMNIMATE basic products
- P on drawing = pitch
- Rated current related to rated cross-section & min. No. of poles.
- Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.
- In the case of a two-pole terminal, the insulating body must be held against the terminal when tightening the screw.
- Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months

## Approvals

Approvals



ROHS

Conform

UL File Number Search

E60693

## Downloads

Brochure/Catalogue

[Catalogues in PDF-format](#)

Creation date April 16, 2021 7:14:49 AM CEST




Catalogue status 09.04.2021 / We reserve the right to make technical changes.

## TPS 5.08/02/90 5.0SN GN BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings




## Recommended wave soldering profiles

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

### Single Wave:



### Double Wave:



### Wave soldering profiles

Wired connection elements should be processed in accordance with the DIN EN 61760-1 standard. We have included two recommendations for practical wave soldering profiles, with which Weidmüller PCB terminals and connectors are qualified.

When choosing a suitable profile for your application, the following factors also need to be considered:

- PCB thickness
- Proportion of Cu in the layers
- Single/double-sided assembly
- Product range
- Heating and cooling rates

The single and double wave profiles each indicate the recommended operating range, including the maximum soldering temperature of 260°C. In practice, the maximum soldering temperature is quite often well below the above maximum profile.

We reserve the right to make technical changes.