

**CABTITE BP 20MM PA**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

**Similar to illustration**

Similar to illustration

The blanking plugs are used for the safe closing of  
unneded cable passages in the sealing elements.

**General ordering data**

Version	Blind plug, Cabtite (cable entry system), Polyamide, red, Height: 22 mm, Width: 20 mm, -60 °C... 100 °C
Order No.	<a href="#">2652440000</a>
Type	CABTITE BP 20MM PA
GTIN (EAN)	4050118662542
Qty.	50 pc(s).

Creation date April 16, 2021 7:17:38 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

**CABTITE BP 20MM PA**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Diameter	20 mm	Height	22 mm
Height (inches)	0.866 inch	Length	22 mm
Length (inches)	0.866 inch	Net weight	4 g
Width	20 mm	Width (inches)	0.787 inch

**Temperatures**

Operating temperature	-60 °C...100 °C
-----------------------	-----------------

**General information**

Halogen	No	Material	Polyamide
---------	----	----------	-----------

**Classifications**

ETIM 6.0	EC000879	ETIM 7.0	EC000879
ECLASS 9.0	27-14-44-21	ECLASS 9.1	27-14-44-21
ECLASS 10.0	27-14-44-21	ECLASS 11.0	27-14-44-21

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">EPLAN</a>
User Documentation	<a href="#">Cabtite Installation Instructions</a>
Brochure/Catalogue	<a href="#">Catalogues in PDF-format</a>