

THM WO VIN 25.4/57.2 SP WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

Version	THM, Conductor and cable markers, 6 - 12 mm, 25.4 x 57.2 mm, white
Order No.	2657190000
Type	THM WO VIN 25.4/57.2 SP WS
GTIN (EAN)	4050118675924
Qty.	400 pc(s).
compatible printer	2599430000 2599440000

Creation date April 16, 2021 7:20:49 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

THM WO VIN 25.4/57.2 SP WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.065 mm	Depth (inches)	0.003 inch
Height	25.4 mm	Height (inches)	1 inch
Net weight	0.2 g	Width	57.2 mm
Width (inches)	2.252 inch		

Temperatures

Operating temperature range	-40...80 °C
-----------------------------	-------------

General data

Adhesive	Polyacrylate adhesive	Approval acc. to UL 969	No
Colour	white	Halogen	Yes
Material	Vinyl film	Number of markers per combination	1 Label reel = Conductor and cable markers
Number per roll	400	Operating temperature range	-40...80 °C
Operating temperature range, max.	80 °C	Operating temperature range, min.	-40 °C
Printing method	Thermal transfer	Type of printing	neutral
UL 94 flammability rating	V-0	Width	57.2 mm

Conductor and cable markers

Conductor O.D.	6 - 12 mm	Conductor O.D., max.	12 mm
Conductor O.D., min.	6 mm	Halogen	Yes
Wire connection cross section AWG, max.	AWG 4	Wire connection cross section AWG, min.	AWG 8

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	Catalogues in PDF-format
--------------------	--

THM WO VIN 25.4/57.2 SP WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

