

FP ENC BS 042 2B**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The FieldPower® housings are highly robust and meet the highest UL flammability class 5 VA.

- The "TS 35 PT6" mounting rail module and PT6 contact unit are easy to snap on.
- Hinged seals allow pre-assembled plug cables to also be used.
- The high cover versions enable the device to be installed.

For cable seals consult accessories.

General ordering data

Order No.	2659710000
Type	FP ENC BS 042 2B
GTIN (EAN)	4050118704075
Qty.	1 pc(s).

FP ENC BS 042 2B

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	42 mm	Depth (inches)	1.654 inch
Height	196 mm	Height (inches)	7.717 inch
Net weight	297.62 g	Width	196 mm
Width (inches)	7.717 inch		

Temperatures

Operating temperature	-40 °C...85 °C
-----------------------	----------------

Classifications

ETIM 6.0	EC000214	ETIM 7.0	EC000214
ECLASS 9.0	27-14-24-09	ECLASS 9.1	27-14-24-09
ECLASS 10.0	27-14-24-09	ECLASS 11.0	27-14-24-09

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
User Documentation	Quick Guide FieldPower Enclosure Size 2 Application Note ur20 FieldPower Size 2
Brochure/Catalogue	Catalogues in PDF-format

FP ENC BS 042 2B

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

