


CMA-41-1000-5A-5VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The pluggable current transformers are particularly suitable for installation on the busbar.

Advantages:

- Screwless connection system with tension-clamp terminal.
- Time-saving connection option for solid and flexible conductors.
- Shock-proof and resistant to vibration, high mechanical retention forces.
- High current resistance

General ordering data

Version	Primary current: 1000 A, Secondary current max.: 5 A, Load: 5 VA, Tolerance class: 0,5, closed current transformer
Order No.	2680210000
Type	CMA-41-1000-5A-5VA-0,5
GTIN (EAN)	4050118696547
Qty.	1 pc(s).

CMA-41-1000-5A-5VA-0,5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	321 g
------------	-------

Dimensions of live conductors

Installation location	Indoor use	Rail	30 x 15 mm, 40 x 10 mm
Round conductor	31 mm	Type of conductor	Insulated conductor only

Electrical attributes

Load	5 VA	Primary current	1,000 A
Secondary current max.	5 A	Tolerance class	0,5

Insulation coordination

Standard	IEC 61869-1: 2007, IEC 61869-2: 2012	Tolerance class	0,5
----------	--------------------------------------	-----------------	-----

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	UL- certificate Certification UL
User Documentation	instruction sheet english.pdf Betriebsanleitung deutsch
Brochure/Catalogue	Catalogues in PDF-format

CMA-41-1000-5A-5VA-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

