

CMA-81-2000-5A-10VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The pluggable current transformers are particularly suitable for installation on the busbar.

Advantages:

- Screwless connection system with tension-clamp terminal.
- Time-saving connection option for solid and flexible conductors.
- Shock-proof and resistant to vibration, high mechanical retention forces.
- High current resistance

General ordering data

Version	Primary current: 2000 A, Secondary current max.: 5 A, Load: 10 VA, Tolerance class: 0,5, closed current transformer
Order No.	2680240000
Type	CMA-81-2000-5A-10VA-0,5
GTIN (EAN)	4050118696592
Qty.	1 pc(s).

CMA-81-2000-5A-10VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	52 mm	Depth (inches)	2.047 inch
Length	134 mm	Length (inches)	5.276 inch
Net weight	999 g	Width	120 mm
Width (inches)	4.724 inch		

Dimensions of live conductors

Installation location	Indoor use	Rail	60 x 30 mm, 80 x 10 mm
Round conductor	54 mm	Type of conductor	Insulated conductor only

Electrical attributes

Load	10 VA	Primary current	2,000 A
Secondary current max.	5 A	Tolerance class	0,5

Insulation coordination

Standard	IEC 61869-1: 2007, IEC 61869-2: 2012	Tolerance class	0,5
----------	--------------------------------------	-----------------	-----

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	UL- certificate Certification UL
User Documentation	instruction sheet english.pdf Betriebsanleitung deutsch
Brochure/Catalogue	Catalogues in PDF-format

CMA-81-2000-5A-10VA-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

