

CMA-101-2500-5A-10VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The pluggable current transformers are particularly suitable for installation on the busbar.

Advantages:

- Screwless connection system with tension-clamp terminal.
- Time-saving connection option for solid and flexible conductors.
- Shock-proof and resistant to vibration, high mechanical retention forces.
- High current resistance

General ordering data

Version	Primary current: 2500 A, Secondary current max.: 5 A, Load: 10 VA, Tolerance class: 0,5, closed current transformer
Order No.	2680250000
Type	CMA-101-2500-5A-10VA-0,5
GTIN (EAN)	4050118696608
Qty.	1 pc(s).

CMA-101-2500-5A-10VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Length	147 mm	Length (inches)	5.787 inch
Net weight	999 g		

Dimensions of live conductors

Installation location	Indoor use	Rail	100 x 10 mm, 80 x 30 mm
Round conductor	70 mm	Type of conductor	Insulated conductor only

Electrical attributes

Load	10 VA	Primary current	2,500 A
Secondary current max.	5 A	Tolerance class	0,5

Insulation coordination

Tolerance class	0,5
-----------------	-----

Classifications

ETIM 6.0	EC002048	ETIM 7.0	EC002048
ECLASS 9.0	27-21-09-02	ECLASS 9.1	27-21-09-02
ECLASS 10.0	27-21-09-02	ECLASS 11.0	27-21-09-02

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	Certification UL
Brochure/Catalogue	Catalogues in PDF-format

CMA-101-2500-5A-10VA-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

