

IE-SFP-1GE-MM-05

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Features of SFP-Transceiver series

- Huge variety of transceiver types for several transmission speeds (100/1000Mbit/s) and distances (up to 60 km)
- BiDi SFP models for communication via single fiber
- Easy control of SFP status due to support of Digital Diagnostic Monitoring (DDM)
- Hot pluggable (during operation)
- Class 1 laser product, EN60825-1 compliant

General ordering data

Version	SFP Transceiver, 1000 Mbps, Multimode, LC-Duplex, 0.5 km, -40 °C...85 °C
Order No.	2682480000
Type	IE-SFP-1GE-MM-05
GTIN (EAN)	4050118692235
Qty.	1 pc(s).

IE-SFP-1GE-MM-05

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	46 g
------------	------

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-40 °C...85 °C
Humidity	5 to 95 % (non-condensing)		

EMC conformity and approvals

EMC standards	EN 55032, EN 55024	Safety standard	UL 60950-1
---------------	--------------------	-----------------	------------

Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating temperature, max.	85 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C		

Fibre optic transceiver characteristics

Transmission rate	1000 Mbps														
Digital diagnostic monitor function (DDM)	Supported														
Transceiver type	Multimode														
Connector type	LC-Duplex														
Transmission distance, typ.	0.5 km														
Wavelength	<table border="1"> <tr> <td>typ.</td> <td>850 nm</td> </tr> <tr> <td>Wavelength</td> <td>TX</td> </tr> <tr> <td>min.</td> <td>830 nm</td> </tr> <tr> <td>max.</td> <td>870 nm</td> </tr> <tr> <td>Wavelength</td> <td>RX</td> </tr> <tr> <td>min.</td> <td>770 nm</td> </tr> <tr> <td>max.</td> <td>870 nm</td> </tr> </table>	typ.	850 nm	Wavelength	TX	min.	830 nm	max.	870 nm	Wavelength	RX	min.	770 nm	max.	870 nm
typ.	850 nm														
Wavelength	TX														
min.	830 nm														
max.	870 nm														
Wavelength	RX														
min.	770 nm														
max.	870 nm														
Receive power	<table border="1"> <tr> <td>min.</td> <td>-18 dBm</td> </tr> <tr> <td>max.</td> <td>-3 dBm</td> </tr> </table>	min.	-18 dBm	max.	-3 dBm										
min.	-18 dBm														
max.	-3 dBm														
Transmission power	<table border="1"> <tr> <td>min.</td> <td>-9 dBm</td> </tr> <tr> <td>max.</td> <td>-3 dBm</td> </tr> </table>	min.	-9 dBm	max.	-3 dBm										
min.	-9 dBm														
max.	-3 dBm														
Link-budget	9 dB														

Guarantee

Time interval	3 years
---------------	---------

Power supply

Voltage supply	3.3 V (via Ethernet switch)
----------------	-----------------------------

Technical data

Type of mounting	Insert in SFP slot
------------------	--------------------

IE-SFP-1GE-MM-05**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-92	ECLASS 9.1	27-44-02-92
ECLASS 10.0	27-44-03-92	ECLASS 11.0	27-44-03-92

Approvals

Approvals



ROHS	Conform
UL File Number Search	E230683

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity RCM Declaration of Conformity
Brochure/Catalogue	Catalogues in PDF-format