

PVN1M1I3SXF3V100TXPX10**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



PV Next: PV-Next, PV generator junction box for combination of 1-6 strings (input and output side) and connection to the inverter. Intelligent innovative design individual for every customer application. Advanced overvoltage protection, optional fuses and switch-disconnectors for optimum operation and safety for the system. In addition, all PV generator junction boxes comply with IEC/EN 61439-2 for maximum reliability of each component.

General ordering data

Version	Photovoltaics, Combiner Box, 1000 V, 1 MPPT, 3 Inputs / 3 Outputs per MPPT, With fuse holder, Surge protection I / II, Cable gland
Order No.	2683030000
Type	PVN1M1I3SXF3V100TXPX10
GTIN (EAN)	4050118699852
Qty.	1 pc(s).

Creation date April 16, 2021 8:05:07 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

PVN1M1I3SXF3V100TXPX10
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com
Technical data
Dimensions and weights

Depth	175 mm	Depth (inches)	6.89 inch
Height	330 mm	Height (inches)	12.992 inch
Net weight	4,467 g	Width	302 mm
Width (inches)	11.89 inch		

Temperatures

Ambient temperature	-25 °C...+50 °C
---------------------	-----------------

Electrical characteristics

Rated DC current per connection	Rated current	10 A	
	Ambient temperature	-25 °C...+50 °C	
	Short-circuit at main output	Duration	10 h
		Factor	1.25 * I _{nc}
Rated DC voltage	1,000 V DC		

Enclosure

Connection type String	Internal terminal (with cable gland feed-through)	Cover	with cover, removeable
Enclosure attachment	Via the four holes under the cover screws	Insulating material	Polyester glass-fibre reinforced, Polycarbonate
Switch disconnecter execution	no switch	Type of mounting	Wall mounting

General data

Installation location	Protected outdoor area (>1 km from sea)	Protection degree	IP65
Standards	IEC 61439-2 ed 2.0, EN 61439-2:2011		

Inputs

Amount of Maximum Power Point Tracking	1 MPPT		
Cartridge fuse	10 x 38 mm		
DC Input + & -	Wire connection	Type of connection	PUSH IN
		Compatible cable crossection	EN 50618:2015, TÜV 2 Pfg 1169/08.07
		Wire cross-section, min.	2.5 mm ²
		Wire cross-section, max.	16 mm ²
Functional earth connector	Cable entry	Number of cable entries	2
		Cable diameter, min.	5 mm
		Cable diameter, max.	10 mm
		Cable glands	M 16
	Wire connection	Type of connection	Screw connection
		Flexible, max. H05(07) V-K	25 mm ²
		w. wire end ferrule, DIN 46228 pt 1, max.	16 mm ²
Fuse type	Empty fuse holder		
Fuse-link standard	IEC 60269-1, IEC 60269-6, gPV (EN 60269-6)		

Creation date April 16, 2021 8:05:07 AM CEST

PVN1M1I3SXF3V100TXPX10

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Max. number of DC inputs	per Maximum Power Point Tracking 3 inputs connected in parallel		
Surge protection auxiliary contact	Wire connection	Type of connection	Tension clamp connection with actuator
		Flexible, max. H05(07) V-K	1.5 mm ²
		w. wire end ferrule, DIN 46228 pt 1, max.	1.5 mm ²
	Cable entry	Number of cable entries	2
		Cable diameter, min.	5 mm
		Cable diameter, max.	10 mm
		Cable glands	M 16

Outputs

DC Output + & -	Wire connection	Type of connection	PUSH IN
		Wire cross-section, min.	2.5 mm ²
		Wire cross-section, max.	16 mm ²

Max. number of DC outputs per Maximum Power Point Tracking 3 outputs connected in parallel

Surge protection DC side

Discharge current I_n (8/20 μ s)	20 kA	Discharge current, max. (8/20 μ s)	40 kA
Lightning test current I_{imp} (10/350 μ s)	6.25 kA	PV system voltage, max. U_{cpv}	1,100 V
Protection level U_p mode (+/-, -/PE, +/- PE)	≤ 3.8 kV	Protection level U_p mode (+/-)	≤ 3.8 kV
Protection level U_p mode (-/PE)	≤ 3.8 kV	Protection level U_p mode (+/PE)	≤ 3.8 kV
Requirements class	Type I/II	Short-circuit current I_{scpv}	11,000 A
Standards	IEC 61439-2 ed 2.0, EN 61439-2:2011	Standby power consumption P_C	< 0.2 W
Surge protection DC side	1000 V type I + II with remote contact, 1000 V type I + II	Total discharge current I_{total} (8/20 μ s)	50 kA
Total discharge current I_{total} (10/350 μ s)	12.5 kA		

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
ECLASS 9.0	22-57-92-03	ECLASS 9.1	22-57-02-90
ECLASS 10.0	22-57-02-90	ECLASS 11.0	22-57-02-92

PVN1M1I3SXF3V1O0TPX10
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com
Technical data
Tender specification sheets

Long specification

Combiner box for inverters
 with 1 Mpp-tracker,
 used to protect the DC
 side. Max. String voltage
 U_{oc}: 1000 V
 MPPT1:
 Up to 3 inputs, connection
 via M25 cable gland with
 3x7mm Ø cable entry (for
 positive and negative one
 each)
 PUSH IN connection / 2.5
 - 6mm² single-wire, multi-
 wire, with/without ferrule
 6 Fuse holder (order fuses
 10x38 separately)
 Up to 3 outputs,
 connection via M25 cable
 gland with 3x7mm Ø
 cable entry (for positive
 and negative one each)
 PUSH IN connection / 2.5
 - 6mm² single-wire, multi-
 wire, with/without ferrule
 without DC switch
 1 surge protection 1000
 V type I + II with remote
 contact
 Connection of the signal
 contact via cable glands
 (8-12mmØ) max. cable
 cross-section: 1.5mm²
 Connection of functional
 earth via cable glands
 (8-12mmØ) cable cross-
 section: 16mm²
 Protection class: IP65
 Plastic enclosure
 Dimensions HxWxD:
 302x302x175 mm
 According to standard,
 Low-voltage switchgear
 assemblies -
 Part 1: General
 specifications, (IEC
 61439-1:2011), BS EN
 61439-2:2011

Important note

Product information

Fuses are not included

Downloads

 Approval/Certificate/Document of
 Conformity

[EU Declaration of Conformity](#)

Engineering Data

[PV Next Schematic Diagram
STEP](#)

User Documentation

[Manual PV Next String Combiner Box
MANUAL PV NEXT IT/ES/FR](#)

Brochure/Catalogue

[Catalogues in PDF-format](#)

Creation date April 16, 2021 8:05:07 AM CEST




PVN1M1I3SXF3V1O0TXPX10

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

PCB design







PVN 1 M2 I6 S0 F3 V1 01 TX PX 10	
Series PVN = PV Next VPU = PV Protect	Voltage 10 = 1kV 15 = 1.5kV
Level 1 = DC trunk box (L1)	Powersupply x = n/a
Series 1 = 1 MPPT supported 2 = 2 MPPT supported 3 = 3 MPPT supported 4 = 4 MPPT supported 5 = 5 MPPT supported 6 = 6 MPPT supported	Monitoring x = n/a
Inputs 1...12 inputs	Output Type 0 = CG 1 = WMAC
Switch x = n/a 0 = manual switch	SPD 2 = TYP II 1 = TYP I+II
	Fuses x = n/a 3 = only fuse holders

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. Weidmüller exclusively reserves the right to file for patents, utility models or designs.

© Weidmüller Interface GmbH & Co. KG

Dimensions without tolerances are no check dimensions

The English version is binding



Darstellung mit Zubehoer
Shown with accessory 0360800000 MF TBF

Nicht im Lieferumfang enthalten!
Not included in delivery!

		Prim PLM Part No.: 1174506		Prim ERP Part No.:	
First Issue Date 29.01.2020	Max. nos.		Weidmüller 		71730 Drawing no. Issue no. Sheet 01 of 01 sheets
	Modification				
		Date	Name	PVN TBF 303018 COMBINERBOX RESIDENTIAL/COMMERCIAL COMBINERBOX RESIDENTIAL/COMMERCIAL	
	Drawn	29.01.2020	Brüntrup, Anna		
Responsible		Wohlgemuth, KI			
Approved	31.01.2020	Püschner, Klau			
Scale: 1/3			Size: A3		
Drawings Customer			Product file:		