

PVN1M1I3S0FXV201TXPX10
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com


PV Next: PV-Next, PV generator junction box for combination of 1-6 strings (input and output side) and connection to the inverter. Intelligent innovative design individual for every customer application. Advanced overvoltage protection, optional fuses and switch-disconnectors for optimum operation and safety for the system. In addition, all PV generator junction boxes comply with IEC/EN 61439-2 for maximum reliability of each component.

General ordering data

Version	Photovoltaics, Combiner Box, 1000 V, 1 MPPT, 3 Inputs / 3 Outputs per MPPT, Surge protection II, Switch disconnecter, WM4C
Order No.	2683400000
Type	PVN1M1I3S0FXV201TXPX10
GTIN (EAN)	4050118700121
Qty.	1 pc(s).

PVN1M1I3S0FXV201TXPX10

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	175 mm	Depth (inches)	6.89 inch
Depth with add-on components	215 mm	Height	302 mm
Height (inches)	11.89 inch	Net weight	2,600 g
Width	186 mm	Width (inches)	7.323 inch

Temperatures

Ambient temperature	-25 °C...+50 °C
---------------------	-----------------

Electrical characteristics

Rated DC current per connection	Rated current	10 A	
	Ambient temperature	-25 °C...+50 °C	
	Short-circuit at main output	Duration	10 h
		Factor	1.25 * I _{nc}
Rated DC voltage	1,000 V DC		
Switching disconnecter capacity	DC-PV-2, IEC 60947-3		

Enclosure

Connection type String	Plug WM4C	Cover	with cover, removeable
Enclosure attachment	Via the four holes under the cover screws	Insulating material	Ployester glass-fibre reinforced, Polycarbonate
Switch disconnecter execution	switch in cover	Type of mounting	Wall mounting

General data

Installation location	Protected outdoor area (>1 km from sea)	Protection degree	IP65
Standards	IEC 61439-2 ed 2.0, EN 61439-2:2011		

Inputs

Amount of Maximum Power Point Tracking	1 MPPT		
DC Input + & -	Wire connection	Type of connection	WM4C plug-in connector
		Compatible cable crossection	EN 50618:2015, TÜV 2 Pfg 1169/08.07
		Wire cross-section, min.	2.5 mm ²
		Wire cross-section, max.	6 mm ²
Functional earth connector	Cable entry	Number of cable entries	1
		Cable diameter, min.	5 mm
		Cable diameter, max.	10 mm
		Cable glands	M 16
	Wire connection	Type of connection	Screw connection
		Flexible, max. H05(07) V-K	25 mm ²
		w. wire end ferrule, DIN 46228 pt 1, max.	16 mm ²
Fuse type	Neither fuse cartridge nor holder		
Max. number of DC inputs	per Maximum Power Point Tracking 3 inputs connected in parallel		

Creation date April 16, 2021 8:08:04 AM CEST

PVN1M1I3S0FXV201TXPX10

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Surge protection auxiliary contact	Wire connection	Type of connection	Tension clamp connection with actuator
		Flexible, max. H05(07) V-K	1.5 mm ²
		w. wire end ferrule, DIN 46228 pt 1, max.	1.5 mm ²
	Cable entry	Number of cable entries	1
		Cable diameter, min.	5 mm
		Cable diameter, max.	10 mm
		Cable glands	M 16

Outputs

DC Output + & -	Wire connection	Type of connection	WM4C plug-in connector
		Compatible cable cross-section	TÜV 2 Pfg 1169/08.07, EN 50618:2015
		Wire cross-section, min.	4 mm ²
		Wire cross-section, max.	6 mm ²

Max. number of DC outputs per Maximum Power Point Tracking 3 outputs connected in parallel

Surge protection DC side

Discharge current I_n (8/20 μ s)	20 kA	Discharge current, max. (8/20 μ s)	40 kA
PV system voltage, max. U_{cpv}	1,100 V	Protection level U_p mode (+/-)	≤ 3.8 kV
Protection level U_p mode (-/PE)	≤ 3.8 kV	Protection level U_p mode (+/PE)	≤ 3.8 kV
Requirements class	Type II	Short-circuit current I_{SCPv}	11,000 A
Standards	IEC 61439-2 ed 2.0, EN 61439-2:2011	Standby power consumption P_C	< 0.2 W
Surge protection DC side	1000 V type II with remote contact, 1000 V type II	Total discharge current I_{total} (8/20 μ s)	50 kA

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
ECLASS 9.0	22-57-92-03	ECLASS 9.1	22-57-02-90
ECLASS 10.0	22-57-02-90	ECLASS 11.0	22-57-02-92

PVN1M1I3S0FXV201TXPX10
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com
Technical data
Tender specification sheets

Long specification

Combiner box for inverters
with 1 Mpp-tracker,
used to protect the DC
side. Max. String voltage
Uoc: 1000 V

MPPT1:
Up to 3 inputs, connection
via WM4 C connector
compatible with cable type
TÜV 2 Pfg1169/08.07 /
EN 50618:2052
Up to 3 outputs,
connection via WM4 C
connector compatible
with cable type TÜV 2
Pfg1169/08.07 / EN
50618:2052

with DC switch
1 surge protection 1000 V
type II with remote contact

Connection of the signal
contact via cable glands
(8-12mmØ) max. cable
cross-section: 1.5mm²
Connection of functional
earth via cable glands
(8-12mmØ) cable cross-
section: 16mm²
Protection class: IP65
Plastic enclosure
Dimensions HxWxD:
186x302x175 mm

According to standard,
Low-voltage switchgear
assemblies -
Part 1: General
specifications, (IEC
61439-1:2011), BS EN
61439-2:2048

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity
Engineering Data	PV Next Schematic Diagram STEP
Technical Documentation	customer drawing
User Documentation	Manual PV Next String Combiner Box MANUAL PV NEXT IT/ES/FR
Brochure/Catalogue	Catalogues in PDF-format



PVN1M1I3S0FXV201TXPX10

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

PCB design






PVN 1 M2 I6 S0 F3 V1 01 TX PX 10									
Series PVN = PV Next VPU = PV Protect									Voltage 10 = 10V 15 = 15.5V
Level 1 = DC trunk box (L1)									Powersupply x = n/a
Series 1 = 1 MPPT supported 2 = 2 MPPT supported 3 = 3 MPPT supported 4 = 4 MPPT supported 5 = 5 MPPT supported 6 = 6 MPPT supported									Monitoring x = n/a
Inputs 1...12 inputs									Output Type 0 = GG 1 = WMAAC
Switch x = n/a 0 = manual switch									SPD 2 = TYP II 1 = TYP I+II
									Fuses x = n/a 3 = only fuse holders

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited.
Offenders will be held liable for the payment of damages. Weidmüller exclusively reserves the right to file for patents, utility models or designs.

© Weidmüller Interface GmbH & Co. KG

Dimensions without tolerances are no check dimensions

The English version is binding



Darstellung mit Zubehoer
Shown with accessory 0360800000 MF TBF

Nicht im Lieferumfang enthalten!
Not included in delivery!

		Prim PLM Part No.: 1215112		Prim ERP Part No.:	
First Issue Date 29.01.2020		Max. nos.		Weidmüller  71728 Drawing no. Issue no. 0 Sheet 01 of 01 sheets	
		Modification			
			Date	Name	
		Drawn	29.01.2020	Brüntrup, Anna	
		Responsible		Wohlgemuth, Kl	
Scale: 1/2 Size: A3		Approved	31.01.2020	Püschner, Klau	
Drawings Customer			Product file:		
PVN TBF 301918 COMBINERBOX RESIDENTIAL/COMMERCIAL COMBINERBOX RESIDENTIAL/COMMERCIAL					