

**BG GHDE FUSE PT6****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The FieldPower® housings are highly robust and meet the highest UL flammability class 5 VA.

- The "TS 35 PT6" mounting rail module and PT6 contact unit are easy to snap on.
- Hinged seals allow pre-assembled plug cables to also be used.
- The high cover versions enable the device to be installed.

For cable seals consult accessories.

**General ordering data**

|            |                                                            |
|------------|------------------------------------------------------------|
| Version    | Enclosures, IP65 with corresponding housing, Polycarbonate |
| Order No.  | <a href="#">2689800000</a>                                 |
| Type       | BG GHDE FUSE PT6                                           |
| GTIN (EAN) | 4050118703108                                              |
| Qty.       | 10 pc(s).                                                  |

**BG GHDE FUSE PT6****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 44 mm      | Depth (inches)  | 1.732 inch |
| Height         | 181 mm     | Height (inches) | 7.126 inch |
| Net weight     | 221 g      | Width           | 104 mm     |
| Width (inches) | 4.094 inch |                 |            |

**Temperatures**

|                     |                |                       |                |
|---------------------|----------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C | Operating temperature | -40 °C...85 °C |
|---------------------|----------------|-----------------------|----------------|

**Environmental Product Compliance**

|            |                                                |
|------------|------------------------------------------------|
| REACH SVHC | Potassium perfluorobutane sulfonate 29420-49-3 |
|------------|------------------------------------------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000747    | ETIM 7.0    | EC000747    |
| ECLASS 9.0  | 27-18-22-04 | ECLASS 9.1  | 27-18-92-90 |
| ECLASS 10.0 | 27-18-22-04 | ECLASS 11.0 | 27-18-22-04 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">Catalogues in PDF-format</a> |
|--------------------|------------------------------------------|

## BG GHDE FUSE PT6

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Drilling template

