



❗ Discontinued

Commercial status

Discontinued: 21 March 2019

Main

Range of product	Multi 9
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
[In] rated current	6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 3 A: 277 V AC - 50/60 Hz 6 A: 12...24 V DC
9 mm pitches	1

Complementary

Range compatibility	Multi 9 C60 Multi 9 C60H-DC Acti 9 iSW-NA
Mounting mode	Fixed
Mounting support	DIN rail
Height	85 mm
Width	9 mm
Depth	73.5 mm
Connections - terminals	Pad terminal1 cable(s) 2.5 mm² - rigid Pad terminal2 cable(s) 1.5 mm² - rigid
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	KEMA ASTA ASEFA LCIE

IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

26928 is replaced by:



electrical auxiliaries M9A26927

Multi 9 - fault contact - 1 SD - 240/415 V AC - 24/130 V DC

Qty 1

Reason for Substitution: End of life | Substitution date: 27 March 2019