

Inline function terminal - IB IL DALI/MM-PAC - 2700605

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, DALI master, Multi-master-capable, integrated DALI power supply unit, safe electrical isolation, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.

It is a multi-master-capable DALI master and is used to control lights with DALI ballasts according to IEC 62386 (formerly IEC 60929).

Furthermore, the terminal supports multi-master operation for communication with Tridonic MSensors.

For integrated DALI bus supply, the terminal requires a 24 V DC supply. This can be implemented automatically via potential jumper U_M or alternatively via connector 1.

Your advantages

- ✓ DALI master with integrated DALI bus supply
- ✓ Sends and receives 2 and 3-byte DALI commands
- ✓ DALI supply can be switched off
- ✓ Suitable for both single and multi-master operation
- ✓ Safe electrical isolation of the DALI bus
- ✓ DALI bus protected against unintentional connection of mains voltage (up to 250 V AC)
- ✓ Communication via process data

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 987103
GTIN	4046356987103
Weight per Piece (excluding packing)	220.000 g
Custom tariff number	85389099
Country of origin	Germany

