

Inline terminal - IB IL 24 DI 16-XC-PAC - 2701154

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline XC, Digital input terminal, Digital inputs: 16, 24 V DC, connection technology: 3-conductor, Extreme conditions version, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

The figure shows the standard item

Product Description

The terminal is designed for use within an Inline station.

It is used to acquire digital signals.

Thanks to special engineering measures and tests, the terminal can be used under extreme ambient conditions.

Your advantages

- ✓ 16 digital inputs
- ✓ Connection of sensors in 2- and 3-conductor technology
- ✓ Maximum permissible load current per sensor: 250 mA
- ✓ Diagnostic and status indicators
- ✓ Can be used under extreme ambient conditions
- ✓ Extended temperature range of -40 °C ... +70 °C (see "Tested successfully: use under extreme ambient conditions" in the data sheet)
- ✓ Coated PCBs

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 713801
GTIN	4046356713801
Weight per Piece (excluding packing)	240.000 g
Custom tariff number	85389091
Country of origin	Germany

