

Inline terminal - IB IL 24 PWR IN/2-F-XC-PAC - 2701162

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline power terminal, version for extreme conditions, complete with accessories (connector and labeling field), 24 V DC, with fuse (main and segment voltage)

The figure shows the standard item

Product Description

The terminal is designed for use within an Inline station. It provides a 24 V supply voltage to the main circuit (U_M) and automatically supplies power for the 24 V segment circuit (U_S). The terminal has protection against polarity reversal and surge voltage. The internal fuse protects the main and segment circuits. Thanks to special engineering measures and tests, the terminal can be used under extreme ambient conditions.

Your advantages

- ✓ Supply of the 24 V main voltage U_M
- ✓ Provision of the 24 V segment voltage U_S
- ✓ Main and segment circuits protected by an internal fuse
- ✓ Can be used under extreme ambient conditions
- ✓ Extended temperature range of -40 °C ... +70 °C (see "Tested successfully: use under extreme ambient conditions" in the data sheet)
- ✓ Coated PCBs



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 713757
GTIN	4046356713757
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85389091
Country of origin	Germany

