

Inline terminal - IB IL 24 DO8/HD-XC-PAC - 2701213

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline XC, Digital output terminal, Digital outputs: 8, 24 V DC, 500 mA, connection technology: 1-conductor, Extreme conditions version, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

The figure shows the standard item

Product Description

The terminal is designed for use within an Inline station.

It is used to output digital signals.

Thanks to special engineering measures and tests, the terminal can be used under extreme ambient conditions.

Your advantages

- ✓ 8 digital outputs
- ✓ Connection of actuators in 1-conductor technology
- ✓ Nominal current per output: 500 mA
- ✓ Total current of the terminal: 4 A
- ✓ Short-circuit and overload-protected outputs
- ✓ Can be used under extreme ambient conditions
- ✓ Extended temperature range of -40 °C ... +70 °C (see "Tested successfully: use under extreme ambient conditions" in the data sheet)
- ✓ Coated PCBs

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 727778
GTIN	4046356727778
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85389091
Country of origin	Germany

