

Inline terminal - IB IL 24/48 DOR 2/W-XC-PAC - 2701214

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline XC, Relay terminal, Relay output: 2 (floating contacts), 2 floating changeover contacts, 24 V AC / 48 V DC, 2 A, for switching ohmic loads, Extreme conditions version, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

The figure shows the standard item

Product Description

The terminal is designed for use within an Inline station.

It has two floating SPDT relay contacts, which are independent of one another.

Thanks to special engineering measures and tests, the terminal can be used under extreme ambient conditions.

Your advantages

- ✓ 2 relays
- ✓ Floating connections for 2 actuators
- ✓ Total current of the terminal: 4 A
- ✓ Diagnostic and status indicators
- ✓ Nominal current per output: 2 A

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 727792
GTIN	4046356727792
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85389091
Country of origin	Germany