

Inline terminal - IB IL 24 DO 2-2A-XC-PAC - 2702133

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline XC, Digital output terminal, Digital outputs: 2, 24 V DC, 2 A, connection technology: 4-conductor, Extreme conditions version, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

The figure shows the standard item

Product Description

The terminal is designed for use within an Inline station.
It is used to output digital signals.

Your advantages

- ✓ 2 digital outputs
- ✓ Connection of actuators in 2-, 3-, and 4-conductor technology
- ✓ Nominal current per output: 2 A
- ✓ Total current of the terminal: 4 A
- ✓ Short-circuit and overload-protected outputs
- ✓ Can be used under extreme ambient conditions
- ✓ Extended temperature range of -40 °C ... +70 °C (see "Tested successfully: use under extreme ambient conditions" in the data sheet)
- ✓ Coated PCBs

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 981781
GTIN	4046356981781
Weight per Piece (excluding packing)	100.000 g
Custom tariff number	85389099
Country of origin	Germany

