

Inline function terminal - IB IL UTH 4/L-ECO - 2702504

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline ECO, Temperature measurement terminal, Analog UTH inputs: 4 (Type L), connection technology: 2-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector

Product Description

The terminal is designed for use within an Inline station.

This terminal can be used to acquire signals from standard thermocouples.

The terminal supports type L thermocouples according to DIN EN 43710.

The measured values are depicted in standardized representation format.

Inline ECO terminals are approved for the temperature range from 0°C to +55°C. The electronics base and Inline connector are supplied as standard.

Your advantages

- ✓ 4 differential inputs for thermocouples
- ✓ Measuring range: -200 °C ... +900 °C
- ✓ Connection of sensors in 2-conductor technology
- ✓ Diagnostic information in the process data word
- ✓ Diagnostic indicator

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 206202
GTIN	4055626206202
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85389099
Country of origin	Germany