

Inline function terminal - IB IL RS 232-ECO - 2702795

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline ECO, communication terminal, serial data transmission, 1 serial input and output channel in RS-232 format, 500 kbps transmission speed in the local bus, IP20 protection, including Inline connector

Product Description

The terminal is designed for use within an Inline station.

The terminal is used to operate standard I/O devices with serial interfaces on a bus system.

Inline ECO terminals are approved for the temperature range from 0°C to +55°C. The electronics base and Inline connector are supplied as standard.

Your advantages

- ✓ One serial RS-232 input and output channel
- ✓ Data is transmitted in transparent mode
- ✓ Transmission speed can be set up to 38400 bps
- ✓ Number of data bits, stop bits and parity can be set
- ✓ RTS and CTS handshake signals available
- ✓ Parameterization via process data
- ✓ Diagnostic and status indicators

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 351629
GTIN	4055626351629
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85389099
Country of origin	Germany