

## FO converters - PSI-MOS-RS422/FO1300 E - 2708575

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fiber optic converter with integrated optical diagnostics, alarm contact, for RS-422/RS-485 4 wire/ INTERBUS up to 2 Mbps, termination device with one fiber optic interface (SC duplex), 1300 nm, for fiberglass cable

### Your advantages

- ✓ Connections can be plugged in via a COMBICON screw terminal block
- ✓ Supply voltage routed through via DIN rail connectors
- ✓ Redundant power supply possible by means of optional system power supply unit
- ✓ High-quality electrical isolation between all interfaces (INTERBUS // FO ports // supply // DIN rail connector)
- ✓ Approved for use in zone 2
- ✓ Floating switch contact for advance warning of critical FO paths
- ✓ Integrated optical diagnostics for continuous monitoring of FO paths
- ✓ Automatic data rate detection for all data rates up to 2 Mbps
- ✓ Shipbuilding approval in accordance with DNV GL



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 176293
GTIN	4046356176293
Weight per Piece (excluding packing)	229.600 g
Custom tariff number	85176200
Country of origin	Germany