

VP HEX M25 PA6 GY**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

General ordering data

Version	Blanking plugs, M 25 x 1.5, 15 mm, Polyamide 6 (PA 6)
Order No.	2715760000
Type	VP HEX M25 PA6 GY
GTIN (EAN)	4050118805420
Qty.	25 pc(s).

VP HEX M25 PA6 GY

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Diameter	32 mm	Height	5.8 mm
Height (inches)	0.228 inch	Length	15 mm
Length (inches)	0.591 inch	Net weight	0.006 g
Width	28 mm	Width (inches)	1.102 inch

Temperatures

Operating temperature	-20 °C...100 °C
-----------------------	-----------------

General information

AF size 1	28 mm	Cable glands	metric
External thread	M 25 x 1.5	Halogen	No
Length of thread	15 mm	Material	Polyamide 6 (PA 6)
Operating temperature range, max.	100 °C	Operating temperature range, min.	-20 °C
Pitch of thread	1.5 mm	Protection degree	IP65, IP68 - 5 bar (30 min.)
Standards	in accordance with UL94 V-2	Tightening torque	2.5 Nm
UL 94 flammability rating	V-2		

Classifications

ETIM 6.0	EC000451	ETIM 7.0	EC000451
ECLASS 9.0	27-14-44-25	ECLASS 9.1	27-14-44-33
ECLASS 10.0	27-14-44-25	ECLASS 11.0	27-14-44-25

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	Catalogues in PDF-format
--------------------	--