

**VP HEX M50 PA6 GY****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

|            |                                                       |
|------------|-------------------------------------------------------|
| Version    | Blanking plugs, M 50 x 1.5, 18 mm, Polyamide 6 (PA 6) |
| Order No.  | <a href="#">2715790000</a>                            |
| Type       | VP HEX M50 PA6 GY                                     |
| GTIN (EAN) | 4050118805444                                         |
| Qty.       | 10 pc(s).                                             |

## VP HEX M50 PA6 GY

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                 |            |                |            |
|-----------------|------------|----------------|------------|
| Diameter        | 63.5 mm    | Height         | 9.5 mm     |
| Height (inches) | 0.374 inch | Length         | 18 mm      |
| Length (inches) | 0.709 inch | Net weight     | 0.035 g    |
| Width           | 55 mm      | Width (inches) | 2.165 inch |

## Temperatures

|                       |                 |
|-----------------------|-----------------|
| Operating temperature | -20 °C...100 °C |
|-----------------------|-----------------|

## General information

|                                   |                             |                                   |                              |
|-----------------------------------|-----------------------------|-----------------------------------|------------------------------|
| AF size 1                         | 55 mm                       | Cable glands                      | metric                       |
| External thread                   | M 50 x 1.5                  | Halogen                           | No                           |
| Length of thread                  | 18 mm                       | Material                          | Polyamide 6 (PA 6)           |
| Operating temperature range, max. | 100 °C                      | Operating temperature range, min. | -20 °C                       |
| Pitch of thread                   | 1.5 mm                      | Protection degree                 | IP65, IP68 - 5 bar (30 min.) |
| Standards                         | in accordance with UL94 V-2 | Tightening torque                 | 8 Nm                         |
| UL 94 flammability rating         | V-2                         |                                   |                              |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000451    | ETIM 7.0    | EC000451    |
| ECLASS 9.0  | 27-14-44-25 | ECLASS 9.1  | 27-14-44-33 |
| ECLASS 10.0 | 27-14-44-25 | ECLASS 11.0 | 27-14-44-25 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">Catalogues in PDF-format</a> |
|--------------------|------------------------------------------|