

D-SUB bus connector - SUBCON-PLUS F2 - 2799490

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB connector, 9-pos. female connector, two 35° cable entries, bus system: CAN, SUCONET K1, K2 (MOELLER), S-BUS (Saia), J-BUS (Merlin Gerin), pin assignment: 2, 3, 4, 5, 7, 9 to two screw connection terminal blocks

Product Description

Two cable infeeds are often required on the D-SUB plugs used in order to build fieldbus systems with RS-485 interfaces. The SUBCON-PLUS plugs range fulfills this requirement and routes the connection to screw terminal blocks – however, duplicated – for two cables. This means clarity during wiring and it simplifies every startup. These plugs are of course also shielded against EMC influences with a metallized housing. In addition, by placing the connection block in either the upper or lower shell, it is possible to select the cable infeed on site from the right or left.

Your advantages

- ✓ Separate terminal blocks for each cable
- ✓ Easy assembly thanks to knurled screws
- ✓ Can be used universally
- ✓ Assembly under field conditions
- ✓ High level of EMC
- ✓ Flexibility in terms of cable entry selection
- ✓ High transmission speed
- ✓ Change to the D-SUB orientation through a reversible connection block



RS-485



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 156305
GTIN	4017918156305
Weight per Piece (excluding packing)	62.670 g
Custom tariff number	85366990
Country of origin	Germany

