

Inline terminal - IB IL AI 8/SF-PAC - 2861412

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Analog input terminal, Analog inputs: 8, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 V ... 25 V, -25 V ... 25 V, 0 V ... 50 V, 0 mA ... 20 mA, 4 mA ... 20 mA, -20 mA ... 20 mA, 0 mA ... 40 mA, -40 mA ... 40 mA, connection technology: 2-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.
It is used to acquire analog voltage and current signals.

Your advantages

- ✓ High measuring accuracy
- ✓ 8 analog single-ended signal inputs for the connection of either voltage or current signals
- ✓ Connection of sensors in 2-conductor technology
- ✓ Current ranges: 0 mA ... 20 mA, 4 mA ... 20 mA, ± 20 mA, 0 mA ... 40 mA, ± 40 mA
- ✓ Voltage ranges: 0 V ... 5 V, ± 5 V, 0 V ... 10 V, ± 10 V, 0 V ... 25 V, ± 25 V, 0 V ... 50 V
- ✓ The channels are parameterized independently of one another via the bus system
- ✓ Measured values can be represented in five different formats
- ✓ 16-bit analog-to-digital converter
- ✓ Process data multiplex mode



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 894351
GTIN	4017918894351
Weight per Piece (excluding packing)	251.700 g
Custom tariff number	85389099
Country of origin	Germany

