

Inline terminal - IB IL AO 2/U/BP-PAC - 2861467

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Analog output terminal, Analog outputs: 2, 0 V ... 10 V, -10 V ... 10 V, connection technology: 2-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

Product Description

The terminal is designed for use within an Inline station. It is used to output analog voltage signals.

Your advantages

- ✓ 2 analog output channels
- ✓ Connection of actuators in 2-conductor technology
- ✓ Voltage ranges: 0 V ... 10 V, ± 10 V
- ✓ Output values can be represented in two different formats
- ✓ Behavior of the outputs in the event of an error can be configured
- ✓ Process data update including conversion time of the digital/analog converter < 1 ms
- ✓ Very good output driver characteristics, making it also suitable for long actuator cables



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 894382
GTIN	4017918894382
Weight per Piece (excluding packing)	96.800 g
Custom tariff number	85389099
Country of origin	Germany