

Inline terminal - IB IL 24 PWR IN/R-PAC - 2861674

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline power terminal or boost terminal, complete with accessories (connector and labeling field), 24 V DC, without fuse

Product Description

The terminal is designed for use within an Inline station.

If the maximum load of the bus coupler for the communications power (U_L) or the supply voltage for the analog terminals (U_{ANA}) is reached, this terminal can be used to provide these voltages again.

To do this, apply a 24 V DC voltage (U_{24V}) to the terminal. The communications power (U_L) and the supply voltage for the analog terminals (U_{ANA}) are generated from this voltage.

In addition, the terminal enables the feed-in of the 24 V DC main voltage (U_M) and the 24 V DC segment voltage (U_S).

Your advantages

- ✓ Supply of all 24 V voltages required for the low-level signal of an Inline station
- ✓ From hardware version 01, approved for use in potentially explosive areas of zone 2



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 894511
GTIN	4017918894511
Weight per Piece (excluding packing)	229.300 g
Custom tariff number	85389099
Country of origin	Germany