

Inline terminal - IB IL 24/230 DOR4/W-PAC - 2861878

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Relay terminal, Relay outputs: 4 (floating contacts), 24 V DC, 230 V AC, for switching ohmic loads, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.

The terminal has four floating relay changeover contacts.

The terminal can be used in the PELV area and in the AC area.

Observe the applicable regulations and safety notes when using the terminal in the AC area.

Features

- Safe isolation according to EN 50178
- Floating connection for four actuators
- Nominal current at the output: 3 A
- Total current of the terminal: 4x 3 A = 12 A
- Diagnostic and status indicators

Your advantages

- ✓ Safe isolation
- ✓ Floating connections for 4 actuators
- ✓ Nominal current at the output: 3 A
- ✓ Total current of the terminal: 3 A
- ✓ Diagnostic and status indicators



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 894573
GTIN	4017918894573
Weight per Piece (excluding packing)	223.800 g
Custom tariff number	85389099
Country of origin	Germany

