

## Inline terminal - IB IL 24/230 DOR4/W-PC-PAC - 2862181

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Relay terminal, Relay outputs: 4 (floating contacts), 24 V DC, 230 V AC, for switching inductive and capacitive loads, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

### Product Description

The terminal is designed for use within an Inline station.  
It has four floating SPDT relay contacts, which are independent of one another.

### Your advantages

- ✓ Safe isolation
- ✓ Nominal current at the output: 3 A
- ✓ Total current of the terminal: 3 A
- ✓ Diagnostic and status indicators



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 017918 894672 |
| GTIN                                 | 4017918894672                                                                                           |
| Weight per Piece (excluding packing) | 224.500 g                                                                                               |
| Custom tariff number                 | 85389091                                                                                                |
| Country of origin                    | Germany                                                                                                 |