

Inline terminal - IB IL AI 2/4-20-PAC - 2862217

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Analog input terminal, Analog inputs: 2, 0 V ... 10 V, -10 V ... 10 V, 0 mA ... 20 mA, 4 mA ... 20 mA, -20 mA ... 20 mA, connection technology: 2-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

The figure shows the IB IL AI 2/SF-PAC

Product Description

The terminal is designed for use within an Inline station. It is used to acquire analog voltage and current signals.

Your advantages

- ✓ 2 analog single-ended signal inputs for the connection of either voltage or current signals
- ✓ Connection of sensors in 2- and 3-conductor technology
- ✓ Current ranges: 0 mA ... 20 mA, 4 mA ... 20 mA, ± 20 mA
- ✓ Measured values can be represented in four different formats
- ✓ Voltage ranges: 0 V ... 10 V, ± 10 V

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 910044
GTIN	4017918910044
Weight per Piece (excluding packing)	100.000 g
Custom tariff number	85389091
Country of origin	Germany