

Inline terminal - IB IL 24 PWR IN/PS-PAC - 2863135

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline power terminal, complete with accessories (connection plug and labeling field), 24 V DC, for system voltages U_M , U_S , U_L , U_{ANA}

The figure shows the version IB IL 24 PWR IN/R-PAC

Product Description

The terminal feeds the voltage to an Inline station if there is no bus terminal module, e.g. in the case of ILC 200 UNI. A 24 V DC voltage (U_{24V}) is applied to the terminal. This provides the logics voltage (U_L) and the supply voltage for the analog terminals (U_{ANA}). The terminal also allows the 24 V DC main voltage (U_M) and the 24 V DC segment voltage (U_S) to be supplied.

Your advantages

- ✓ Supplies all 24 V DC voltages required for the low-level signal
- ✓ Diagnostic and status indicators

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 917265
GTIN	4017918917265
Weight per Piece (excluding packing)	226.200 g
Custom tariff number	85389099
Country of origin	Germany