

Temperature measuring transducer - MINI MCR-SL-PT100-UI-200-SP - 2864192

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



MCR temperature transducer, can be configured, for Pt 100 temperature sensors, with spring-cage connection, order configuration. Replacement part: 2902051 MINI MCR-2-RTD-UI-PT-C.

Your advantages

- ✓ Power supply possible via the foot element (TBUS)
- ✓ Optimized temperature measuring range of -50°C to +200°C for increased accuracy
- ✓ For 2-, 3-, 4-conductor Pt 100 sensors in accordance with IEC 60751
- ✓ Error indication via diagnostic LED and analog signal
- ✓ Input and output signals can be configured via DIP switches
- ✓ 3-way isolation
- ✓ Pt 100 signals to create standard signals
- ✓ Highly-compact temperature transducer for electrical isolation, conversion, amplification, and filtering of



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 142502
GTIN	4046356142502
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85437090
Country of origin	Germany