

## Loop-powered isolators - MINI MCR-SL-2CP-I-I-SP - 2864781

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



MCR passive isolator, two-channel, for electrical isolation of current signals without supply voltage, with spring-cage connection.

Replacement item: 2864655 MINI MCR-SL-2CP-I-I

### Your advantages

- ✓ Voltage drop at isolating amplifier of just 1.7 V
- ✓ Does not require additional auxiliary voltage
- ✓ Two channels on a design width of just 6.2 mm
- ✓ Highly compact 2-conductor passive isolators for the electrical isolation and filtering of standard analog signals
- ✓ Supplied by an input loop



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 017918 974961 |
| GTIN                                 | 4017918974961                                                                                           |
| Weight per Piece (excluding packing) | 80.200 g                                                                                                |
| Custom tariff number                 | 85437090                                                                                                |
| Country of origin                    | Germany                                                                                                 |