

Inline terminal - IB IL AI 4/EF-PAC - 2878447

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Analog input terminal, Analog inputs: 4, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 mA ... 20 mA, 4 mA ... 20 mA, -20 mA ... 20 mA, connection technology: 2-, 3-, 4-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.
It is used to acquire analog voltage and current signals.

Your advantages

- ✓ Short update time of 1 ms, maximum for all channels
- ✓ Sensor supply with channel-specific integrated short-circuit and overload protection
- ✓ Bus-synchronous provision of input values with very low jitter (< 10 µs)
- ✓ Measured value acquisition with 16-bit resolution
- ✓ 4 differential signal inputs
- ✓ Connection of sensors in 2-, 3-, and 4-conductor technology
- ✓ Current ranges: 0 mA ... 20 mA, 4 mA ... 20 mA, ±20 mA
- ✓ Voltage ranges: 0 V ... 10 V, ±10 V, 0 V ... 5 V, ±5 V
- ✓ Short-circuit
- ✓ Diagnostic and status indicators

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 996376
GTIN	4017918996376
Weight per Piece (excluding packing)	251.100 g
Custom tariff number	85389091
Country of origin	Germany

