

Industrial Ethernet Switch - FL SWITCH 3004T-FX ST - 2891034

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Managed Ethernet switch with four RJ45 ports at 10/100 Mbps, one ST format fiber optic port and operating temperature of -40°C ... +75°C

Product Description

FL SWITCH 3000 managed industrial Ethernet switches combine extensive network performance and security features with complete IEEE redundancy (STP/RSTP/MST) and 15 ms recovery time extended ring redundancy. Unique web customization provides a simplified user interface for today's applications and scalable functionality for future needs. A comprehensive mix of fiber optic and copper port connections meets a wide range of applications.

Your advantages

- ✓ RJ45 ports support a transmission speed of 10/100 Mbps
- ✓ Fiber-optic ports support 100 Mbps
- ✓ -40 to 75°C and -10 to 60°C ambient temperature versions
- ✓ Secure web-based and SNMP-based management
- ✓ Security options with cable locking
- ✓ Extensive web diagnostics with configurable LED and remote alarm contacts
- ✓ Unique cleanup function hides unused configuration pages, reducing complexity, maintenance and startup times
- ✓ Auto negotiation and autocrossing detection simplifies installation and setup

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 659154
GTIN	4046356659154
Weight per Piece (excluding packing)	1,250.000 g
Custom tariff number	85176200
Country of origin	Taiwan

