

Industrial Ethernet Switch - FL SWITCH 3016T - 2891059

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Managed Ethernet switch with 16 RJ45 ports at 10/100 Mbps and operating temperature of -40°C ... +75°C

Product Description

FL SWITCH 3000 managed industrial Ethernet switches combine extensive network performance and security features with complete IEEE redundancy (STP/RSTP/MST) and 15 ms recovery time extended ring redundancy. Unique web customization provides a simplified user interface for today's applications and scalable functionality for future needs. A comprehensive mix of fiber optic and copper port connections meets a wide range of applications.

Your advantages

- ✓ -40 to 75°C and -10 to 60°C ambient temperature versions
- ✓ RJ45 ports support a transmission speed of 10/100 Mbps
- ✓ Fiber-optic ports support 100 Mbps
- ✓ Security options with cable locking
- ✓ Extensive web diagnostics with configurable LED and remote alarm contacts
- ✓ Secure web-based and SNMP-based management
- ✓ Unique cleanup function hides unused configuration pages, reducing complexity, maintenance and startup times
- ✓ Auto negotiation and autocrossing detection simplifies installation and setup

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 764278
GTIN	4046356764278
Weight per Piece (excluding packing)	1,540.000 g
Custom tariff number	85176200
Country of origin	Taiwan

