

Industrial Ethernet Switch - FL SWITCH SFN 14TX/2FX - 2891935

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ethernet switch, 14 TP RJ45 ports, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function. Two FO ports in SC format.

Product Description

Standard function Ethernet switch with 14 RJ45 ports and 2 SC-D fiber optic ports. Provides automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function, 12 V DC ... 48 V DC input voltage, redundant power supply capable with remote alarming.

Your advantages

- ✓ RJ45 ports support a transmission speed of 10/100 Mbps
- ✓ Fiber-optic ports support 100 Mbps
- ✓ 16 ports in a narrow metal housing with redundant input voltage
- ✓ Security options with cable locking
- ✓ Local diagnostic indicators with LEDs
- ✓ Devices are available for the standard temperature range (0 °C ... 60 °C) and wide temperature range (-40 °C ... 75 °C)
- ✓ Auto negotiation and autocrossing detection simplifies installation and setup

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 551601
GTIN	4046356551601
Weight per Piece (excluding packing)	1,060.000 g
Custom tariff number	85176200
Country of origin	Taiwan