

Inline function terminal - IB IL 24 LSKIP-PAC - 2897457

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Coupler terminal, for extending the Inline local bus, transmission speed in the local bus: 500 kbps / 2 Mbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.

Using this terminal in connection with the IB IL 24 FLM-PAC terminal, you can extend an Inline station over two or more rows. To do so, install the IB IL 24 FLM-PAC terminal in an Inline station at the end of the row and the Inline coupler terminal at the beginning of the next row. This connection is a restricted-length local bus extension.

Apply the supply voltages to the terminal again. To do this, apply a 24 V DC voltage (U_{24V}) to the terminal. The communications power (U_L) and the supply voltage for the analog terminals (U_{ANA}) are generated internally from this voltage.

In addition, you can apply the 24 V DC main voltage (U_M) and the 24 V DC segment voltage (U_S) to the terminal.

Your advantages

- ✓ Supply of all 24 V voltages required for the low-level signal of an Inline station
- ✓ Data transmission between terminals IB IL 24 FLM-PAC and IB IL 24 LSKIP-PAC via the RS-422 protocol

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 165419
GTIN	4046356165419
Weight per Piece (excluding packing)	241.200 g
Custom tariff number	85389099
Country of origin	Germany