

Inline terminal - IB IL 24/230 DOR4/HC-PAC - 2897716

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, Relay terminal, Relay outputs: 4 (floating contacts), 24 V DC, 230 V AC, high inrush current, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.

It has four floating relay contacts.

The terminal can be used in the PELV area and in the AC area.

Observe the applicable regulations and safety notes when using the terminal in the AC area.

Features

- Safe isolation according to EN 50178
- Floating connection for four actuators
- Nominal current at the output: 10 A
- High inrush current

Your advantages

- ✓ Floating connections for 4 actuators
- ✓ Nominal current 10 A
- ✓ Safe isolation
- ✓ Low power consumption through use of bistable relays
- ✓ Diagnostic and status indicators

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 133081
GTIN	4046356133081
Weight per Piece (excluding packing)	260.000 g
Custom tariff number	85389099
Country of origin	Germany

