

Communication module - IB IL DALI/PWR-PAC - 2897813

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, DALI master, integrated DALI power supply unit, safe electrical isolation, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connectors and marking fields

Product Description

The terminal is designed for use within an Inline station.

It represents a DALI master that can control up to 63 DALI ballasts.

The IB IL DALI/PWR-PAC has an integrated DALI power supply unit. It can be extended with up to 3 additional IB IL DALI-PAC DALI masters.

Your advantages

- ✓ Safe electrical isolation of the DALI bus
- ✓ Indicators for diagnostics, transmission, and reception
- ✓ Protection of the DALI bus against accidental connection of the mains voltage (up to 250 V AC)
- ✓ Up to 64 DALI devices per master terminal
- ✓ Function blocks for PC Worx are available

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 133067
GTIN	4046356133067
Weight per Piece (excluding packing)	280.000 g
Custom tariff number	85389099
Country of origin	Germany