

## Communication module - IB IL DALI-PAC - 2897910

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline, DALI master, Extension for IB IL DALI/PWR-PAC, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

### Product Description

The terminal is designed for use within an Inline station.  
It represents a DALI master that can control up to 63 DALI ballasts.  
The IB IL DALI-PAC is an extension terminal for the IB IL DALI/PWR-PAC.  
Up to 3 IB IL DALI-PAC can be connected downstream of the IB IL DALI/PWR-PAC.

### Your advantages

- ✓ DALI master without integrated DALI bus supply
- ✓ DALI bus protected against unintentional connection of mains voltage (up to 250 V AC)
- ✓ Diagnostic and status indicators

**RoHS**

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 046356 133074 |
| GTIN                                 | 4046356133074                                                                                           |
| Weight per Piece (excluding packing) | 80.000 g                                                                                                |
| Custom tariff number                 | 85389099                                                                                                |
| Country of origin                    | Germany                                                                                                 |