

Constant voltage source - MINI MCR-SL-CVS-24-5-10-SP-NC - 2902823

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Constant voltage source, input voltage: 9.6 V DC ... 30 V DC, output voltage: 10 V, 7.5 V, 5 V, 2.5 V DC, electrically isolated, can be configured via DIP switches, spring-cage connection technology, standard configuration. Replacement part: 2902065 MINI MCR-2-CVCS-PT.

Product Description

The 6.2 mm wide configurable MINI MCR-SL-CVS-24-10-5 constant voltage source is used to generate high precision constant voltages.

The input voltage can fall between 9.6 V DC and 30 V DC.

The DIP switches accessible from the side of the housing enable configuration of the 10 V DC, 5 V DC, 7.5 V DC, and 2.5 V DC output voltages.

The input voltage can be applied either via connection terminal blocks on the modules or in conjunction with the DIN rail connector.

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 682435
GTIN	4046356682435
Weight per Piece (excluding packing)	100.000 g
Custom tariff number	85437090
Country of origin	Germany