

Module carrier - TC-2D37SUB-DO16-ESD-AR-UNI - 2902913

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Universal termination carrier for redundantly connecting 16 PSR-FSP modules to digital output cards, via two D-SUB connectors, 37-pos. (1:1 connection). Solution for Emergency Shut Down (ESD) applications.

Your advantages

- Mechanically decoupled PCB
- Robust aluminum profile with integrated DIN rail
- Side parts with integrated end clamps
- Redundant D-SUB pin strip system connection, 37-pos. (1:1 connection)
- Simple or redundant supply, decoupled from diode, protected against polarity reversal
- Error message in the event of power supply failure or fuse fault
- Relay output (N/O contact, floating) and flashing LED for error message
- Undervoltage monitoring at input at < 18 V DC
- Suitable for safe state off applications
- Cable sets for signal connection are not supplied as standard and must be ordered separately



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 703703
GTIN	4046356703703
Weight per Piece (excluding packing)	1,500.000 g
Custom tariff number	85366990
Country of origin	Germany