

Module carrier - TC-2KS50-DO16-F&G-AR-RS - 2904112

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination carrier for redundantly connecting 16 PSR-ETP modules to digital output cards of the Yokogawa ProSafe-RS controller, via two KS50 connectors, 50-pos. Solution for Fire & Gas (F&G) applications. Suitable for Yokogawa SDV541 card.

Your advantages

- ✓ Mechanically decoupled PCB
- ✓ Robust aluminum profile with integrated DIN rail
- ✓ Side parts with integrated end clamps
- ✓ Redundant system connection, 50-pos. (KS/AKB-compatible)
- ✓ Simple or redundant supply, decoupled from diode, protected against polarity reversal
- ✓ Error message in the event of power supply failure or fuse fault
- ✓ Relay output (N/O contact, floating) and flashing LED for error message
- ✓ Undervoltage monitoring at input at < 18 V DC
- ✓ Suitable for safe state on applications
- ✓ Cable sets for signal connection are not supplied as standard and must be ordered separately

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 783736
GTIN	4046356783736
Custom tariff number	85366990
Country of origin	Germany