

Module carrier - TC-2KS50-DO32-EX-PR-CS - 2905199

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination Carrier for redundantly connecting 32 MACX Analog Ex i solenoid drivers to digital output cards of the Yokogawa Centum VP controller, via two KS50 connectors, 50-pos. Suitable for Yokogawa ADV551 and ADV561 cards.

Your advantages

- ✓ Mechanically decoupled, passive PCB
- ✓ Redundant system connection, 50-pos. (KS/AKB-compatible)
- ✓ Simple or redundant supply (decoupled from diode, protected against polarity reversal) and monitoring function implemented via separate DIN rail module
- ✓ Robust aluminum profile with integrated DIN rail
- ✓ Side parts with integrated end clamps
- ✓ Cable sets for signal connection are supplied as standard and do not have to be ordered separately

RoHS

Key Commercial Data

Packing unit	1
GTIN	 4 046356 950756
GTIN	4046356950756
Custom tariff number	85366990

Articles in set

Cable set - TC-C-MAX2-SC-31320000 - 2902425



Cable set for signal transmission on the Termination Carrier for modules from the MACX Analog Ex series. Connection of terminal points 3.1 and 3.2 (signal transmission) to the signal PCB.

Module carrier - TC-2KS50-DO32-EX-PR-CS - 2905199

Articles in set

Cable set - TC-C-PTB3-SC-SET1 - 2905216



Cable set for TC-MACX-MCR-PTB power and fault signaling module (Item No. 2904673), for use on the Termination Carrier for signal conditioners from the MACX Analog Ex series.