

Module carrier - TC-2KS40-AO16-M-PRH-CS - 2905905

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination Carrier for redundantly connecting 16 MINI Analog signal conditioners to analog input cards of the Yokogawa CENTUM VP controller, via KS40 connector, 40-pos. Suitable for Yokogawa card AAI543.

Your advantages

- ✓ Mechanically decoupled, passive PCB
- ✓ Redundant system connection, 40-pos. (KS/AKB-compatible)
- ✓ Simple or redundant supply (decoupled from diode, protected against polarity reversal) and monitoring function implemented via separate DIN rail module
- ✓ FLK26 high-density HART connection
- ✓ Robust aluminum profile with integrated DIN rail
- ✓ Side parts with integrated end clamps
- ✓ Cable sets for signal connection are supplied as standard and do not have to be ordered separately



Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 |
| GTIN |  4 055626 019048 |
| GTIN | 4055626019048 |
| Custom tariff number | 85366990 |

Articles in set

Cable set - TC-C-2MIN-AI-05061516 - 2905224



Cable set for signal transmission on the termination carrier for modules from the MINI Analog series. Connection of terminal points 5 and 6 of two adjacent MINI Analog modules to the signal PCB via a 4-pos. PTSM connector.

Module carrier - TC-2KS40-AO16-M-PRH-CS - 2905905

Articles in set

Cable set - TC-C-PTB1-AI-SET1 - 2905217



Cable set for MINI MCR-SL-PTB-FM power module (Item No. 2902958) and MINI MCR-SL-FM-RC-NC error message module (Item No. 2902961), for use on the termination carrier for modules from the MINI Analog series.

DIN rail bus connectors - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728



DIN rail connector for DIN rail mounting. Universal for TBUS housing. Gold-plated contacts, 5-pos.
