

Module carrier - TC-D37SUB-AIO16-MP-PS-UNI - 2906640

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



Universal Termination Carrier for connecting 16 MINI Analog Pro signal conditioners to digital or analog I/O cards, via D-SUB connector, 37-pos. (1:1 connection), with HART multiplexer connection

Your advantages

- ✓ Mechanically decoupled, passive PCB
- ✓ Robust aluminum profile with integrated DIN rail
- ✓ Side parts with integrated end clamps
- ✓ D-SUB pin strip system connection, 37-pos. (1:1 connection)
- ✓ Simple or redundant supply (decoupled from diode, protected against polarity reversal) and monitoring function implemented via separate DIN rail module
- ✓ Interface for connection to HART multiplexer
- ✓ Cable sets for signal connection are supplied as standard and do not have to be ordered separately

RoHS

Key Commercial Data

Packing unit	1
GTIN	 4 055626 119960
GTIN	4055626119960
Custom tariff number	85366990

Articles in set

Cable set - TC-C-2PRO-PT-05061516 - 2905914



Cable set for signal transmission on the Termination Carrier for modules from the MINI Analog Pro series. Connection of terminal points 5 and 6 of two adjacent MINI Analog Pro modules to the signal PCB via a 4-pos. PTSM connector.

Module carrier - TC-D37SUB-AIO16-MP-PS-UNI - 2906640

Articles in set

Cable set - TC-C-PTBP-PT-SET1 - 2905915



Cable set for MINI MCR-2-PTB-PT power module (Item No. 2902958) and MINI MCR-2-FM-RC-PT fault signaling module (Item No. 2904508), for use on the Termination Carrier for modules from the MINI Analog Pro series.