

Safety module - IB IL 24 LPSDO 8-PAC - 2916024

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Safety-related digital output module, IP20 protection, for the SafetyBridge system. The module has four safe digital outputs with two-channel occupancy or 8 safe digital outputs with single-channel occupancy

Product Description

The safety module is an output module from the Inline product range and is used in a SafetyBridge system. The safety module can be used as a part of an Inline station at any point within an INTERBUS, PROFINET or PROFIBUS system. The transmission speed of the safety module can be set to 500 kbaud or 2 Mbaud using a switch. Only one transmission speed must be used uniformly within a station. The module has four safe digital outputs with two-channel occupancy or eight safe digital outputs with single-channel occupancy. In the SafetyBridge system, you can achieve the following safety integrity by using this safety module depending on the installation and parameterization:

- up to category 4 according to EN 954-1 standard,
- up to SIL 3 according to EN 61508 standard,
- up to SIL CL 3 according to EN 62061 standard,
- up to PL e according to EN ISO 13849-1 standard.

Your advantages

- ✓ Generation and monitoring of the SafetyBridge protocol
- ✓ Processing of the parameterized safety logic
- ✓ SIL 3 according to IEC 61508/EN 61508
- ✓ SIL 3 in accordance with EN 62061
- ✓ PL e in accordance with EN ISO 13849-1



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 479110
GTIN	4046356479110
Weight per Piece (excluding packing)	240.000 g
Custom tariff number	85389091
Country of origin	Germany

