

Temperature measuring transducer - MACX MCR-SL-RTD-I-SP-NC - 2924320

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Temperature transducer, converts signals from resistance temperature detectors and resistors into 0/4 - 20 mA analog signals. Freely programmable, 3-way electrical isolation. Replacement item: 1050201 MACX MCR-RTD-I-SP.

Your advantages

- ✓ Power supply possible via DIN rail connector
- ✓ Installation in zone 2, protection type "n" (EN 60079-15) permitted
- ✓ Programming during operation and also voltage-free using IFS-USB-PROG-ADAPTER programming adapter
- ✓ 3-way electrical isolation
- ✓ Configuration via software (FDT/DTM): sensor type, connection technology, measuring range, measuring unit, filter, alarm signal, and output range
- ✓ 0 ... 20 mA or 4 ... 20 mA output
- ✓ Input for resistance thermometers and resistance-type sensors
- ✓ Status indicator for supply voltage, cable, sensor, and module errors



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 503884
GTIN	4046356503884
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85437090
Country of origin	Germany