

Temperature measuring transducer - MACX MCR-EX-T-UI-UP-SP - 2924689

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Programmable Ex-i temperature transducer with analog output and 1 limit value relay, standard configuration, resistance thermometer in 2-, 3-, or 4-conductor technology, thermocouples, electrical isolation, wide-range power supply, Push-in connection, SIL, PL.

Your advantages

- ✓ Input for resistance thermometers, thermocouples, resistance-type sensors, potentiometers, and mV sources, [Ex ia] IIC
- ✓ Programming during operation with Ex measuring circuit connected and also voltage-free using IFS-USB-PROG-ADAPTER programming adapter
- ✓ Cold junction compensation with separate plug
- ✓ Configuration via software (FDT/DTM) or IFS-OP-UNIT operator interface and display unit
- ✓ Up to SIL 2 according to EN 61508
- ✓ Installation in zone 2, protection type "n" (EN 60079-15) permitted
- ✓ Plug-in screw or spring-cage connection technology (Push-in technology)
- ✓ Status indicator for supply voltage, cable, sensor, and module errors
- ✓ Measure differential temperatures
- ✓ Wide-range power supply of 19.2 ... 253 V AC/DC
- ✓ Freely programmable input and output
- ✓ Inverse output signal ranges as an option
- ✓ Relay switching output



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 629102
GTIN	4046356629102
Weight per Piece (excluding packing)	180.000 g
Custom tariff number	85437090

Temperature measuring transducer - MACX MCR-EX-T-UI-UP-SP - 2924689

Country of origin	Germany
-------------------	---------

Phoenix Contact 2022 © - all rights reserved
<http://www.phoenixcontact.com>